

Entry-level models With upgrade opportunities



FROMMM | WRAPPING SOLUTIONS

FS325 & FS335
Stretch Wrapping Machines

www.frommpackaging.ca

FS325 & FS335



The FS325 & FS335 Entry-level models form the basis of the FROMM FS380 Series Stretch wrapping machines. Making use of FS380 Technology, you can rely on many available options. Their modular construction, carriage upgrades and attractive purchase price offers many expansion options for almost all budgets and user requirements. A wide variety of branded parts, including electronics and motors, optimizes operational reliability and reduces maintenance requirements to a minimum. High Safety and Ease of use is inherent in their design. This makes them an attractive alternative in any purchasing process.

Speak with your FROMM representative for the extensive product range possibilities.

Some basic technical details of the FS325 & FS335

- Power: 230V-50/60Hz - 1ph - 1,0 Kw. - 6.0A
- Programs - PLC up to 6 programs
- Max. capacity* up to 25 pallets / hr. (* depending on pallet dimensions, configuration,
- Processes pre-stretched or standard stretch films from 8 – 23 micron
- Wrapping height, max. 2.450 mm. (96.5") - pallet included
- Photosensors for load detection
- Rotation speed, adjustable between 5 - 12 rpm.
- Soft start & stop as standard
- Vertical—up & down—carriage speed, independently adjustable between 1,3 and 5,4 m/min. (4 and 14 ft/min.)
- Machine dimensions : Height: min. 1.480 - (58.2") max. 2.700 mm (106") / width and length depending on the selected turntable type and diameter.
- Commercial inverters
- Standard turntable, max load 2.000Kgs. (4,409 lbs). Optional, increased weight load up to 3.000kg (6,613 lbs)
- Loading ramps available for standard and heavy loads
- Floor mounting frame, recessed into the floor

FS325 specific

- Film carriage CA2 mechanical brake,
- Turntable sizes available - 1.500 (std) & 1.650 mm (59" & 65")

FS335 specific

- Film carriages, choice of 3 types; CA2 mechanical brake, CA4 magnetic brake and CA6 One-motor Pre-stretch (with gears for 150, 200 and 250%).
- Retrospective carriage upgrade possibilities
- Film roping, multiple film strip cutting and film end cutting
- Turntable sizes available - 1.500 (std) , 1.650, 1.800, 2.200, 2.400 and 2.600 mm (59", 65", 71", 87", 95" and 102")
- Ultra-Low 25 mm (1") turntable of 1.650 mm (65"), max. load capacity 1.200 Kg. (2,645 lbs)
- "Horse-shoe" turntable, dimensions 1.650 (65") or 1.800 mm (71"). Max. load capacity 1.200 Kg. (2,645 lbs)
- Load weighing systems

Let's take a look at the benefits

- Economic all-rounder for productive and energy efficient working
- Compact - low freight costs and easy to move.
- Easy installation - plug and play—no special installation required
- Requires virtually no maintenance
- Excellent human interface and easy to operate for multiple operators
- Extensive choice of options and modular design makes this machine easily adaptable