



Automatic Side-Seal Strapping Machine

The SQ-800Y with brushless DC Motor is a side-seal model which boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection.

Wide Adaptability to Fully-Automated Packaging Line

The machine fits any existing or proposed conveyor system, adapts to any conveyor height and requires no special equipment.

Several options are available to make it easy to integrate the SQ-800Y into a conveyor system. Larger arch sizes offer a wide range of applications, particularly for large and heavy packages.

■ Strapping Speed

Standard strapping rate is 50 straps/min, even when tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.







SQ-800Y

Standard Specifications (Arch size 600 mm wide x 850 mm high or 23" wide x 33" high)

Dimension	Width	1500 mm	59-1/8 in.
	Height	1723 mm	67-3/4 in.
	Depth	610 mm	24 in.
	Weight	180 kg	397 lbs.
Package Size	Max	W 580 X H 820 mm	W 22-7/8 X H 32-1/4 in.
	Min	W 30 X H 80 mm	W 1-1/4 X H 3-1/8 in.
Joint / Strap		heat seal / polypropylene	heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2 in.
Strap Tension		784 N (80 kgf) 150mm stroke	176 lbf 6 in. stroke
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA	

Dimensions and specifications are subject to change without notice.

Modification rights reserved. ISO 9001 and 14001 Certified © 2020 FROMM PACKAGING SYSTEMS CANADA



DISTRIBUTED BY:



FROMM PACKAGING SYSTEMS CANADA

676 Monarch Ave. Unit 6 Ajax, ON L1S 4S2 Email: sales@frommpackaging.ca

Tel: 905-428-3444