

FROMMM | PACKAGING
SYSTEMS

Steel Strapping Tools



Manual sealless steel strapping tools

Manual sealless strapping tools are ideal for flat goods such as pallets, crates, bales and all kinds of packages. The tools are characterized by their reliability, strength, ergonomic design principles and service friendliness. The proven sealless joint permits extremely rational working, reducing strapping costs by ca. 10%. The strength of the sealless joint is very uniform and normally higher than that of joints with seals.



A332/A333

Tried and tested universal tools for all applications. Reliable, rugged and service-friendly. Characterized by their simple operation and light weight, the A332 and A333 have become indispensable helpers worldwide. Both types are available with the torque wrench tensioning system (TW model).

Strap quality:

Regular duty steel strap (Uniflex) up to 850 N/mm²

Strap dimensions:

9.5 – 13.0 x 0.38 – 0.50 mm (A332)
12.7 – 20.0 x 0.38 – 0.58 mm (A333)

Weights:

A332: 3.3 kg, A333: 3.9 kg (standard model)
A332: 3.7 kg, A333: 4.3 kg (TW model)



A335

The A335 is identical in design to the A333 but is fitted with a specially machined feed wheel and gripper and is therefore suitable for use **with high tensile steel strapping bands**. Also available with the torque wrench tensioning system (TW model).

Strap quality:

High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

12.7 – 19.0 x 0.50 – 0.58 mm

Weights:

3.9 kg (standard model)
4.3 kg (TW model)



A337

with MicroLock™ safety joint

An ideal tool for a wide range of vertical and horizontal strapping applications for flat goods in almost all industries. The unique innovative punching of the sealless MicroLock™ joint guarantees even greater safety. Opening and closing by the recoil effect is rendered impossible. The MicroLock™ seal is very popular for strapping packages which for instance are subject to shrinkage due to drying out.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

9.5 – 20.0 x 0.38 – 0.63 mm

Weights:

4.45 kg (standard model)
4.70 kg (TW model)



A338

The special gearing permits **very high strap tension** of a maximum of 5500 N with a force of only 240 N. A handy tool suitable for flat goods and characterized by its convenience and strength.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

12.7 – 19.0 x 0.50 – 0.70 mm

Weights:

5.7 kg (standard model)
5.9 kg (TW model)



Punched sealless joint



Manual steel strapping tools with a seal joint

The tools described here are designed for round objects and goods with small surfaces. An exception is the manual tensioner A301 used in combination with the manual sealer A412 and designed especially for large flat objects with a long band take-up.

The joint requires seal joints and thanks to the ideal lever configuration, these can be produced with minimal force. The average strength of the double notch joint with seals is ca. 75%.



A301

Manual tensioner A301 is specially designed for flat objects and packages. Thanks to the feed wheel tensioning system an unlimited band take-up is permitted, guaranteeing taut tension with no tension loss. Using manual sealer model A412 the double notch joint is produced in one operation. The ideally curved levers prevent the handle from jamming, guaranteeing rational working with no risk of hand injury.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

Tensioner: 19.0 – 32.0 x 0.50 – 1.00 mm

Weight:

4.0 kg



A402

Model A402 is especially well suited for round packages with a very small supporting surface. Here too an unlimited take-up is possible and the double notch joint is produced using the manual sealer A412.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

Tensioner: 19.0 – 32.0 x 0.63 – 1.00 mm

Weight:

4.0 kg



A412

Sealing tool A412 is used in combination with the manual flat or round tensioners A301/A402. The double notch joint is mounted in a single operation permitting only perfect notch joints thanks to the built-in safety pawl.

The ideally curved levers prevent the handle from jamming, guaranteeing rational working with no risk of hand injury. The rubber spacer on the lower lever also permits sealing with both hands on the upper lever.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

Sealer: 19.0 – 32.0 x 0.63 – 1.00 mm

Weight:

3.4 kg



A431

This lightweight and handy combination strapping tool is ideal for strapping bars, tubes, bundles and goods with an extremely small surface. Simple to operate and totally independent of any energy source the A431 has become established as the ideal helper. Lap-over seals provided with a single notch joint are used for sealing.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

10.0 – 19.0 x 0.38 – 0.63 mm

Weight:

3.4 kg




Single notch joint



Pneumatic sealless steel strapping tools

Areas of application for pneumatic, sealless strapping tools are identical to those for manual tools. The same also applies to the characteristics of the sealless notched joint. The essential advantage is in faster strapping, uniformly and ideally tensioned straps plus the efficient mode of working.

Time savings are considerable, particularly when long band take-ups are required, for instance with compressible packed goods and extremely large crates and pallets. Pneumatically powered tools combined with semi-automatic strap feed systems increase productivity even further.



A380

The A380 is used mainly in the timber and construction material industry. The massively constructed tool is characterized in particular by its reliability in shift work and with continuous operation under the most rigorous conditions. Supplied as a semi and fully automatic model, it is also produced in four tensioning levels. It is recommended to use the tool in suspended mode.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

12.7 – 25.0 x 0.50 – 1.00 mm

Weights:

17.4 and 18.4 kg (with suspension bracket)

Strap tensions:

4500 N, 6500 N, 7500 N, 9500 N

Models:

Single button = fully automatic
Two-button = semi-automatic



A383

The A383 is the big brother of the A380. Heavier and larger, it is intended for the same industries. Also available in two models; especially suitable for 25 and 32 mm wide steel straps.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

19.0 – 32.0 x 0.63 – 1.30 mm

Weight:

24.0 kg (incl. suspension bracket)

Strap tensions:

10000 N, 15000 N



A385

The high-performance tool with MicroLock™ sealless joint has been designed for stationary applications. It tensions, seals and cuts the strapping off by pressing the appropriate buttons. Available in various tension versions and suitable for regular and high tensile steel strapping. Regular strap tension is provided by pneumatic tensioning and the security sealless MicroLock™ joint guarantees perfectly secured goods.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

9.5 – 20.0 x 0.38 – 0.63 mm

Weights:

10.5 kg (incl. suspension bracket)

Tension versions:

2200 N, 3500 N, 4100 N, 6500 N



A390/A391

Semi-automatic strapping tools for the pneumatic tensioning and manual sealless joining of steel straps. The pneumatic drive for the tensioning system guarantees fast and uniform tensioning. The low tool weight (5.1 kg) permits efficient working without the need for suspension.

Strap qualities:

A390:
Regular duty steel strap (Uniflex) up to 850 N/mm²
A391:
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

9.5 – 20.0 x 0.38 – 0.58 mm

Weight:

5.1 kg (A390/A391)

Max. tension:

6000 N



Punched sealless joint



Pneumatic steel strapping tools with a seal joint

The strapping applications of the pneumatically powered steel strapping tools with a seal joint are identical to those of the manual tools. These tools are especially suitable for round, curved and irregular shaped goods with a small surface. Separate lap-over metal seals are used for the joint; these form a single or double notch joint, guaranteeing a correct seal every time.



A480

Due to its low weight the A480 does not necessarily have to be suspended. This permits more mobile operation. Ideal for strapping tubes, wire coils and all kinds of small bundles, it is a handy and popular tool in numerous industries. Available in two different tensioning levels.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

10.0 – 19.0 x 0.38 – 0.63 mm

Weight:

4.6 kg (with suspension bracket)

Strap tensions:

2500 N, 4500 N



A482

Due to its low weight the A482 does not necessarily have to be suspended. Straps of up to 0.90 mm thickness can be processed. The perfect double notch joint guarantees a strength of 75 %. The modern A482 optimizes the strapping of packages, mainly in the metal industry.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

19.0 x 0.63 – 0.90 mm

Weight:

7.0 kg (with suspension bracket)

Strap tensions:

4000 N, 7000 N



A483

Heavier and larger than the A482, the A483 is suitable for use in the same industries. Also supplied in two models, its main application is with 25 and 32 mm wide steel straps. Its pneumatically raised feed wheel greatly assists the introduction of heavy steel straps. Ideal for strapping steel coils, tubes and rods in all positions, as it can be fitted with four different suspension brackets. The A483 has proved its worth especially under shift and continuous working conditions.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

25.0 – 32.0 x 0.80 – 1.00 mm

Weight:

19.5 kg (incl. suspension bracket)

Strap tensions:

7000 N, 9000 N

Models:

Single button = fully automatic
Two-button = semi-automatic



A452

Pneumatic pusher type tensioner A452 is characterized by its very high strap tension force of 8500 N. Thanks to its free-wheeling system, no strap tension is lost on completion of the tensioning cycle. This extremely rugged, fast and lightweight tool is suitable for both mobile and stationary applications.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

19.0 – 32.0 x 0.63 – 1.27 mm

Weight:

4.35 kg

Max. tension:

8500 N



A461

Pneumatic sealer A461 used for joints can be operated single-handed. It is fitted with a safety mechanism which prevents poor seal joints resulting from faulty operation.

Strap qualities:

Regular duty steel strap (Uniflex) up to 850 N/mm²
High tensile steel strap (Ultraflex) up to 1100 N/mm²

Strap dimensions:

19.0 – 32.0 x 0.63 – 1.00 mm

Weight:

4.2 kg



Double notch joint

Contact Us:

FROMM Packaging Systems Canada
Unit 6, 676 Monarch Ave, Ajax
ON, Canada, L1S 4S2
Sales@frommpackaging.ca

905-428-3444
WWW.FROMMPACKAGING.CA

Further information: www.frommpackaging.ca